


Technical data sheet

Series terminals 10 mm², polypropylene

Item number: 2056716



Tested according to EN 60998. Steel terminals, steel screws, electrogalvanised, 12-pin, individual terminals detachable from strips using "twist'n'pull". Captive upwards screw. Max. approved ambient temperature to EN 60998: -5 to +80 °C. Nominal cross-section 10 ± mm² Nominal voltage 450 V Nominal current 57 A Max. connections per side: 10 mm² rigid or 6 mm² flexible.



PP Polypropylene

Master data

Item number	2056716
Type	76 CE WS/ORLK 10
Description 1	Terminal strip
Available from	01.12.2025
Manufacturer	OBO
Dimension	10mm ²
Colour	White
Material	Polypropylene
Smallest sales unit	500
Unit of quantity	Piece
Weight	4.13 kg
Weight unit	kg/100 pc.


Technical data sheet

Series terminals 10 mm², polypropylene

Item number: 2056716



Dimensions



Length	134 mm
Width	23 mm
Height	17 mm

Technical data

Closing plate required	no
Connectable conductor cross-section, single-wire, max.	10 mm ²
Connectable conductor cross-section, single-wire, min.	2.5 mm ²
Connectable conductor cross-section, fine-wire without wire-end ferrule, max.	6 mm ²
Connectable conductor cross-section, fine-wire without wire-end ferrule, min.	2.5 mm ²
Connectable conductor cross-section, multi-wire, max.	6 mm ²
Connectable conductor cross-section, multi-wire, min.	2.5 mm ²
Connection position	Side
No. of terminals	12
Number of screwless terminals per pole	2
Version of electrical connection 1	Screw connection
Version of electrical connection 2	Screw connection
Drill hole spacing, centre	11.5 mm
Explosion-tested version	no
Suitable for flexible conductors	yes
Suitable for solid conductors	yes
Suitable for multi-wire conductors	yes
Mounting type	Direct mounting
Nominal cross-section, min.	10 mm ²
Nominal voltage	450 V
Nominal current	57 A
Pole number	12
Cross-section	Max. connections per side: 10 mm ² rigid or 6 mm ² flexible mm ²
Screw tightening torque	0.8 kN/m
Permitted temperature range, max.	80 °C
Permitted temperature range, min.	-5 °C

Technical data sheet

Series terminals 10 mm², polypropylene

Item number: 2056716



Technical data

Transparent	no
Ambient temperature	80 °C