

Technical data sheet

Bolt tie FAZ II P A5

Item number: 3498996



Bolt tie FAZ II Plus for the anchoring of medium to heavy loads in cracked or uncracked concrete. Suitable for high loads with small edge and axial distances. For knocking in.
European Technical Assessment ETA-99/0520, including characteristic values under fire exposure to fire resistance R 120.
Proof of suitability in the event of seismic impacts, categories C1 and C2.




A5 Stainless steel

Master data

| | |
|---------------------|------------------|
| Item number | 3498996 |
| Type | FAZIIPlus12/10A5 |
| Description 1 | Bolt anchor |
| Manufacturer | OBO |
| Dimension | M12x110 |
| Colour | stainless steel |
| Material | Stainless steel |
| Smallest sales unit | 20 |
| Unit of quantity | Piece |
| Weight | 9.63 kg |
| Weight unit | kg/100 pc. |

Dimensions



| | |
|-------------|--------|
| Length | 104 mm |
| Dimension L | 104 mm |

Technical data sheet

Bolt tie FAZ II P A5

Item number: 3498996



Technical data

| | |
|---------------------------|------------------|
| Version for | For pushing in |
| Anchor/nail/bolt version | Spreading anchor |
| Drill hole diameter, min. | 12 mm |
| Thread | M12 |
| Thread metric | 12 |
| Thread type | Metric |
| Thread length | 59 mm |
| Approvals available | yes |
| Clamping range, max. | 25 mm |
| Clamping range, min. | 10 mm |