Technical data sheet

Trunking unit, blank, height 60-110 mm

Item number: 7424420





Ready-to-mount trunking unit with three blanking lids for cable laying, consisting of the trunking base (floor trough with side and floor covering contact profiles) and trunking lid. Floor trough with holding straps for self-contacting mounting of separating retainers. The scope of delivery contains 6 height-adjustable fixing brackets, 6 screed anchors and lid butt seals (3x for nominal trunking widths of 200 and 300) or height-adjustable lid butt supports: 3x for nominal trunking width 400 and 6x for nominal trunking widths 500 and 600. Trunking lid screwed on for delivery.



St

Steel

FS

Strip galvanized

Master data

Item number	7424420	
Туре	OKA-W2006050	
Description 1	Flushfloor trunking unit	
Description 2	blank	
Manufacturer	OBO	
Dimension	2400x200x60	
Material	Steel	
Surface	Strip galvanized	
Surface standard	DIN EN 10346	
Smallest sales unit	2.4	
Unit of quantity	Metre	
Weight	1004.2 kg	
Weight unit	kg/100 m	
CO2 Footprint (GWP) Cradle-to- Gate	48,8821 kg CO2e / 1 Meter	



Technical data sheet

Trunking unit, blank, height 60-110 mm

Item number: 7424420



Technical data		
Mounti	ng opening cover	no
Covers	3	3
Numbe	er of mounting openings	0
Numbe	er of insertable partitions	1
units	er of planned flush-mount	3
Numbe	er of compartments	2 St.
Mounti	ng system fastening type	Floor
Floor p		yes
Cover	fastening, locking	no
	stallation option	yes
Installa tank	ation opening for on-floor	no
Decou	plable	no
Suitabl	e for expansion joint	no
Mesh v	wall	no
Trunkir	ng height, max.	110 mm
Duct he	eight, min.	60 mm
Cover	material thickness	4
Minimu	ım screed height	60
With co	onnection opening	no
With ed	quipotential bonding	no
With se	eparating retainer	no
With o	verhang	yes
Mounti	ng opening	Without
	-adjustment range, max.	110 mm
	-adjustment range, min.	60 mm
	cross-section	5200 mm²
	able cover	yes
Separa	ating retainer fastening	rasten

Lock

Separating retainer fastening Separating retainer fastening