Technical data sheet

Cross-over 60 A2

Item number: 7027501



Cross-over for the creation of a horizontal branch, fitting for lock and screw-on cable trays of side height 60 mm. Screwless mounting with double clamps or screw connection with FRS truss-head screws and M6 combination nut. Can be used indoors and outdoors. Fastening material must be ordered separately.



CER

A2

Stainless steel

2B

Bright, treated

Master data


Item number 7027501 Description 1 Cross over Description 2 for cable tray Manufacturer OBO Dimension 60x100 Colour stainless steel Material Stainless steel Surface Bright, treated Surface standard Smallest sales unit 1 Unit of quantity Piece		
Description 2 for cable tray Manufacturer OBO Dimension 60x100 Colour stainless steel Material Stainless steel Surface Bright, treated Surface standard Smallest sales unit 1	Item number	7027501
Manufacturer OBO Dimension 60x100 Colour stainless steel Material Stainless steel Surface Bright, treated Surface standard Smallest sales unit 1	Description 1	Cross over
Dimension 60x100 Colour stainless steel Material Stainless steel Surface Bright, treated Surface standard Smallest sales unit 1	Description 2	for cable tray
Colour stainless steel Material Stainless steel Surface Bright, treated Surface standard Smallest sales unit 1	Manufacturer	OBO
Material Stainless steel Surface Bright, treated Surface standard Smallest sales unit 1	Dimension	60x100
Surface Bright, treated Surface standard Smallest sales unit 1	Colour	stainless steel
Surface standard Smallest sales unit 1	Material	Stainless steel
Smallest sales unit 1	Surface	Bright, treated
	Surface standard	
Unit of quantity Piece	Smallest sales unit	1
	Unit of quantity	Piece
Weight 88.4 kg	Weight	88.4 kg
Weight unit kg/100 pc.	Weight unit	kg/100 pc.

Technical data sheet

Cross-over 60 A2

Item number: 7027501





100 mm
60 mm
0.8 mm
100 mm

Technical data

Connector version	Integrated connector
Maintain electrical functions	yes
Material thickness, floor plate	0.8 mm
NATO hole pattern	no
Rustproof steel, pickled	no
Permitted temperature range, max.	120 °C
Permitted temperature range, min.	-20 °C
Wide-span version	no
Type of connector, cable support system	screwed/clamped
Recommended quantity of bolts	20 St.
Rail thickness	1.25 mm