

Technical data sheet

US 5 suspended support FTK, black

Item number: 6341684



Suspended support made from U profile with welded-on head plate, perforated to 3 sides, for the creation of support constructions for cable trays. Suitable for mounting on horizontal concrete ceilings and steel supports. Wall and support bracket can be mounted on both sides of the U suspended support. Spacer DSK to insert, from bracket width 400 mm or when mounting the bracket on the end of the suspended support. With black powder coating.



St Steel

P135 PES135 - Polyester

Master data

Item number	6341684
Type	US 5 K 40 FTK SW
Description 1	Support
Description 2	with welded head plate
Manufacturer	OBO
Dimension	50x50x400
Colour	Jet black; RAL 9005
Material	Steel
Surface	PES135 - Polyester
Surface standard	
Smallest sales unit	1
Unit of quantity	Piece
Weight	136.8 kg
Weight unit	kg/100 pc.


Technical data sheet

US 5 suspended support FTK, black

Item number: 6341684



Dimensions



Length	400 mm
Width	50 mm
Height	50 mm
Dimension L	400 mm

Technical data

Version for	U profile
Bracket length 200	5.75 kN
Bracket length 400	3.1 kN
Bracket length 600	2.2 kN
Maintain electrical functions	yes
Material thickness	2.5 mm
Maximum tensile load	10 kN
With tothing	no