Technical data sheet Empty housing X 02

Item number: 2005594





Junction box for the connection of cables and lines indoors and in outdoor areas. Square design without entries. Suitable for wall and ceiling mounting with the option to fasten outside, inside or to mount via the corner domes. Particularly impact resistant with IK09. Cover with quick lock, sealable. Made from halogen-free and UV-resistant materials.

Junction box according to EN 60670. Impact resistance IK09 according to EN 50102. Protection rating IP67 according to EN 60529.

















Polycarbonate

М	_	_	4.		_	_	_	4-
IVI	ы	S	т	-1	Г.	О	н	та

2005594
X02C SW
Empty Enclosure
OBO
95x95x72
Graphite black; RAL 9011
Polycarbonate
1
Piece
17.5 kg
kg/100 pc.
0,7382 kg COe / 1 Piece


Technical data sheet Empty housing X 02





Dimensions ZZ

Length	95 mm
Width	95 mm
Height	72 mm



Technical data

Cover fastening Screwed Shape Square Suitable for outdoor use yes Clear internal dimensions 85x85x57 mm with lid yes Mounting type Surface-mounted Protection rating IP67 Protection rating IK code IK09 Protection class II Permitted temperature range. 60 °C
Suitable for outdoor use yes Clear internal dimensions 85x85x57 mm with lid yes Mounting type Surface-mounted Protection rating IF code IK09 Protection class II
Clear internal dimensions 85x85x57 mm with lid yes Mounting type Surface-mounted Protection rating IF code IK09 Protection class II
with lid yes Mounting type Surface-mounted Protection rating IP67 Protection rating IK code IK09 Protection class II
Mounting type Surface-mounted Protection rating IF code IK09 Protection class II
Protection rating IP67 Protection rating IK code IK09 Protection class II
Protection rating IK code IK09 Protection class II
Protection class II
Permitted temperature range 60 °C
max.
Permitted temperature range, min5 °C
Weatherproof yes