# Technical data sheet

## Spacer clip ASL 733, black

## Item number: 1362870




Spacer clip in black, for the installation of pipes and cables on walls, ceilings and floors. With self-locking cover. Fastening via slot.
Approved for the maintenance of electrical function according to DIN 4102 Part 12, maintenance of electrical function classes E 30 to E 90.

CE UKCA E30 E60 E90

| | |
|---|---|
| St | Steel |
| G | Electrogalvanised |

### Master data


| | |
|---|---|
| Item number | 1362870 |
| Type | ASL 733 17 SW |
| Description 1 | Distance saddle |
| Description 2 | with slot |
| Manufacturer | OBO |
| Dimension | 14-17mm |
| Colour | Jet black; RAL 9005 |
| Material | Steel |
| Surface | Electrogalvanised |
| Surface standard | EN ISO 19598 / EN ISO 4042 |
| Smallest sales unit | 25 |
| Unit of quantity | Piece |
| Weight | 2.099 kg |
| Weight unit | kg/100 pc. |

# Technical data sheet

## Spacer clip ASL 733, black

## Item number: 1362870

### Dimensions




| | |
|---|---|
| Length | 44 mm |
| Width | 14 mm |
| Height | 29 mm |

### Technical data

| | |
|---|---|
| Distance to the wall | yes |
| Number of cables/pipes | 1 |
| Version for | Closed |
| Fastening type | Screw hole |
| For diameter | 14 - 17 |
| Halogen-free | yes |
| Material thickness | 1.5 mm |
| Clamping range D, max. | 17 mm |
| Clamping range D, min. | 14 mm |
| UV-resistant | yes |