
Technical data sheet

Cross-connector for round and flat conductors FT

Item number: 5312655



- Meets the requirements of VDE 0185-305-3 (IEC/ EN 62305-3)
- Fit: Rd 8-10 x FL 30
- Mounted with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8

St	Steel
FT	Hot-dip galvanised

Master data


Item number	5312655
Type	252 8-10XFL30 FT
Description 1	Cross-connectors
Manufacturer	OBO
Dimension	8-10mm
Material	Steel
Surface	Hot-dip galvanised
Surface standard	DIN EN ISO 1461
Smallest sales unit	25
Unit of quantity	Piece
Weight	22.4 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	0,5026 kg CO2e / 1 Piece

Technical data sheet

Cross-connector for round and flat conductors FT

Item number: 5312655

Dimensions



Dimension A	60 mm
Dimension B	60 mm

Technical data

Type of fastening screw	Hexagonal bolt
Type of connector	Cross-connectors
Lightning current carrying capacity	H/100 kA
Suitable for connection	Round conductor Rd 8-10 / flat conductor Fl 30
Fit	Rd 8-10/FL30 mm
ROHS-conformant	yes
Intermediate plate	no